



kaleidescape™

# Kaleidescape Movie Player 2

KPLAYER-5000



- **Elegant 1U design**
- **Imports DVD video (including home videos) or audio CD**
- **Rack or free-standing installation**
- **Downloadable designs, modules and programs available for integration with Crestron and AMX touch panels**
- **Downloadable files available for popular universal remote controls**

The Kaleidescape Movie Player 2, with its integral CD/DVD combo drive, is a high-performance audio/video component designed to import and play back movies and music in a Kaleidescape System. The elegant 1U low-profile design can be rack-mounted or, with side bezels, used free-standing on a shelf. The built-in combo drive imports CDs and DVDs and supports direct-from-disc playback like a standard DVD player. You can play a DVD without waiting to import it, or play borrowed and rented DVDs without importing them at all, eliminating the need for a separate DVD player.

Movie Player 2 can play HD and DVD movies from a Kaleidescape Server to a display device in the digital domain without any analog processing. Dolby™ Digital, DTS, MPEG, and PCM audio formats are fully supported. The High-Definition Multimedia Interface (HDMI™) and component video connections deliver reference-quality video. Movie Player 2 can be integrated with control systems via an extensive bi-directional control protocol over RS-232 or TCP/IP. IR control is also available. Control protocol and configuration options enable seamless integration with and automatic control of audio and video processors, movie projectors, display devices, control systems, lighting systems, screen-masking systems, and audio systems.



Optional white side bezels shown  
for free-standing installations.

Contoured edges of faceplate  
provide a finished look by partially  
concealing the rack screws.



## KPLAYER-5000 Specifications

### Video Outputs

- HDMI (w/HDCP™)
- Component YPbPr (BNC)
- S-Video
- Composite (BNC)

### Video Output Formats

- NTSC 480i, 480p
- PAL 576i, 576p
- High-definition 720p, 1080i at 50 and 60 Hz
- Progressive scan using DCDi by Faroudja

### Audio Outputs

- HDMI
- Digital, coaxial (BNC) and optical (TosLink)
- Analog stereo (RCA)

### Audio Output Formats

- Dolby
- DTS
- MPEG Audio
- PCM

### Disc Media

- CD Audio, CD-R, CD-RW, DVD, DVD-R, DVD-RW, DVD+R, DVD+RW, DualDisc

### Connections

- 100Base-TX Ethernet (RJ45)
- RS-232 for control systems (DB-9 male)
- IR front-bezel window, IR-in 1/8" mini jack

### Dimensions (w x h x d)

- 17.5 in x 1.7 in x 13.8 inches (44.5 cm x 4.3 cm x 35 cm) without side bezels
- 1 rack unit

### Weight

- 10 pounds (4.6 kg)

### Power

- 100-240V, 50-60Hz universal input
- 0.5A consumption

### Environmental

- Operating: 5 to 35°C (41 to 95°F)
- Storage: -20 to 60°C (-4 to 140°F)
- Relative humidity: 5% to 90% non-condensing
- Thermal output: 171 BTU/hr maximum
- Airflow: 2.5 CFM

### Certifications

- CSA (IEC 60950-1:2001, CSA 60950-1-03, UL 60950-1)
- FCC Class B, CE
- RoHS compliant
- Dolby
- Macrovision™
- HDMI



kaleidescape

Kaleidescape, Inc.  
520 Logue Avenue  
Mountain View, CA 94043 USA  
+1 (650) 625-6100  
Toll Free within the US: (888) 352-5343  
[www.kaleidescape.com](http://www.kaleidescape.com)

© Kaleidescape, Inc. All rights reserved.  
Kaleidescape and the Kaleidescape logo are trademarks of Kaleidescape, Inc. and may be registered in some jurisdictions. Other product and brand names are the trademarks of their respective third-party holders and may be registered in some jurisdictions.

Kaleidescape Part No. 101-0040 Rev. B