

easy access and connection.

& Belgium-France.

effective and easy to install.

a table thickness 3" or less.

TBUS-2

ADVANCED TABLE/PODIUM MOUNT POP-UP CABLE MANAGEMENT SYSTEM



gently on the lid which hydraulically raises the TBUS-2 connectors for

Modular Design - Dual 110V AC (USA) or single 220V AC & 5

Available 220V AC Power Sockets - UK, Germany-EU, Italy, Australia

Elegant and Rugged Rectangular Design - Sturdy and attractive anodized aluminum enclosure designed to provide maximum connectivity in the smallest possible footprint, at the same time cost-

standard size wall plate insert slots (inserts optional).

	SPECIFICATIONS	
	POWER SOURCE (AC POWER LIMITS):	Dual US 110V AC, 60 Hz, 2.5A per connector. Australia 220-240V AC, 50/60 Hz, 5A per connector. Germany and the EU 220-240V AC, 50/60 Hz, 5A per connector. Belgium and France 220-240V AC, 50/60 Hz, 5A per connector. The UK 220-240V AC, 50/60 Hz, 5A per connector. South Africa 220-240V AC, 50/60 Hz, 5A per connector. Italy 220-240V AC, 50/60 Hz, 5A per connector.
	DIMENSIONS:	Including the outer rim: 25.3cm x 16.6cm x 18.4cm (9.97" x 6.53" x 7.25") W, D, H. Without the outer rim: 24cm x 15.6cm x 18.4cm (9.47" x 6.03" x 7.25") W, D, H.
DESCRIPTION	WEIGHT:	1.5kg (3.3lbs) approx.
The TBUS-2 is a rectangular table-mount cable management system for	ACCESSORIES:	Attached power cord.
boardrooms and conference rooms. It opens/closes by pressing down	OPTIONS:	Kramer's Wall Plates modules.

Size - Requires a cutout 9.470" (240.54mm) x 6.03" (156.13mm) and

© www.kramerelectronics.com 2008