

# mio modero r-4 remote



## PERFECT COMBINATION

The Mio Modero R-4 combines all of the great features of the stylish Mio Modero R-series but is also equipped with a full-color LCD Touch Panel and ZigBee wireless technology, giving it a virtually unlimited coverage area, two-way communication and unlimited control of devices. Signals are transmitted through walls, ceilings, etc. with a range of up to 100 feet indoors (dependent upon conditions); however the R-4's coverage area can be extended to almost any distance by using AMX NetLinx Repeaters. And with ZigBee, any number of R-4s can be used within the same property without interfering with each other.

## A TOUCH OF BEAUTY

The R-4's 2.4-inch full-color, active-matrix TFT LCD Touch Panel comes ready to control any device connected to the AMX Control System. It's like having a full-size AMX Touch Panel in the palm of your hand giving you instant system control just by touching any of the animated or static icons on the touch panel. With ZigBee two-way communication, you'll also be able to receive device status confirmation and dynamic lists such as artist, album, song or movie title.

## UNLIMITED CONTROL

The R-4 includes 29 hard buttons and 2 LCD touch panel buttons to give the user thousands of options for managing all of the operating functions of each device. In the center of the remote resides a large circular chrome button that acts as a simplified navigation tool - up, down, left, right and select. Positioned adjacent are two square, chrome buttons programmed to change channels and adjust volume levels.



# mio modero r-4 remote

## MIO-R4 (FG148-04)

---

### LCD TOUCH PANEL DISPLAY

- 2.4" color active-matrix TFT (240 x 320 pixel resolution)
- Viewing Angle: +/- 60° horizontal, +/- 60° vertical
- Display colors: 64K (16-bit color depth)
- Brightness: 100 cd/m2
- Contrast: 350:1

### PUSHBUTTONS

- 29 hard buttons, 2 LCD buttons

### SUPPORTS

- Unlimited number of devices connected to the AMX control system

### CUSTOMIZATION

- Multiple languages supported for Touch Panel and Engraved Buttons

### LANGUAGES SUPPORTED

- English
- Spanish
- French
- Italian
- German
- Portuguese
- Arabic
- Mandarin Chinese
- Russian
- Japanese
- Thai
- Hindi
- Korean
- Greek

### RF TRANSMISSION

- ZigBee 2.4 GHz, 2-way network communications

### RF TRANSMISSION RANGE

- 100 feet indoors (extendable using AMX NetLink Repeaters)

### 4-WAY BACK LIT SYSTEM

- Capacitive Touch
- Tilt Switch
- Push Button
- Touch Screen

### INCLUDES

- Mio Modero R-Series Charging Cradle
- Mio Modero Lithium-Ion Rechargeable Battery

### ENCLOSURE MATERIALS

- Molded IR/RF Transmissive Material
- Black brushed metal top and bottom cover plates
- Chrome side rails, Volume, Channel, Navigation, Select, Play, and Power buttons

### WEIGHT

- .65 lbs (25g) with battery

### POWER

- Mio Modero Lithium-Ion Rechargeable Battery
- 12-18 VDC Power Supply for recharging battery

### DIMENSIONS (HWD)

- 9.5" x 2" x .74" (241.3mm x 50.8mm x 18.8mm)

### OPERATING ENVIRONMENT

- Operating Temperature: 0° to 50° C (32° to 122° F)
- Storage Temperature: -10° to 70° C (14° to 158° F)



ARGENTINA • AUSTRALIA • BELGIUM • BRAZIL • CANADA • CHINA • ENGLAND • FRANCE • GERMANY • GREECE • HONG KONG • INDIA • INDONESIA • ITALY • JAPAN  
LEBANON • MALAYSIA • MEXICO • NETHERLANDS • NEW ZEALAND • PHILIPPINES • PORTUGAL • RUSSIA • SINGAPORE • SPAIN • SWITZERLAND • THAILAND • TURKEY • USA  
ATLANTA • BOSTON • CHICAGO • CLEVELAND • DALLAS • DENVER • INDIANAPOLIS • LOS ANGELES • MINNEAPOLIS • PHILADELPHIA • PHOENIX • PORTLAND • SPOKANE • TAMPA  
3000 RESEARCH DRIVE, RICHARDSON, TX 75082 • 800.222.0193 • 469.624.8000 • +1.469.624.7400 • 469.624.7153 fax • www.amx.com