Isys Wall Mount Touchpanels overview

Crestron's wall mount touchpanels are elegantly designed to provide a perfect flush mount control solution for all types of applications. A single touchpanel can provide the ideal centralized controller for a facility full of equipment. Or, multiple touchpanels can be deployed throughout a home or commercial facility to provide extensive multipoint control of a large AV distribution or automation system. Whatever the application, with a complete range of sizes available, lsys Wall Mount Touchpanels provide the ideal combination of performance, programmability, and versatile installation.

Every one of Crestron's tilt touchpanel models, from 6.4" to 17" widescreen, is also offered in an attractive flush mount version designed for lectern, wall, and rack mount installations. Each model features the same high performance and connectivity as its tilt model counterpart. Fresh, modern styling with backlit hard buttons, front-firing speakers and integral microphone provide exceptional function and great looks.

For homes and offices requiring a smaller, more cost-effective solution, Crestron offers the compact **Isys TPS-4L** 3.6" Wall Mount Touchpanel. Its bright active matrix color touchscreen and high-speed Ethernet connectivity deliver a very powerful and elegant user interface in the space of a common keypad or light switch. Also available, the **Isys TPS-2000L** affords a 5" touchpanel solution with video and intercom capabilities that's affordable enough to put one in every room.

All Isys Wall Mount Touchpanels are available in a choice of black or white, with additional designer colors and finishes available for models 10.4" and smaller.



Typical Isys Wall Mount Touchpanel Application using Crestron Home® CAT5 AV

See end of section for additional diagrams



Isys Wall Mount Touchpanels cross reference

	Isys Wall Mount Touchpanels							
i	TPS-17L	TPS-15L	TPS-12L	TPS-4000L	TPS-3100L			
Touchscreen Display								
Display Size	17"	15"	12"	10.4"	6.4"			
Aspect Ratio	15:9 WXGA	4:3 XGA	4:3 SVGA	4:3 VGA	4:3 VGA			
Resolution	1280 x 768	1024 x 768	800 x 600	640 x 480	640 x 480			
Color Depth	24-bit 16.7M	24-bit 16.7M	18-bit 256k	18-bit 256k	18-bit 256k			
	24-DIL 10.7W	24-bit 10.7M	TO-DIL 200K	TO-DIL ZOOK	TO-DIL 200K			
Fouchpanel Graphics								
Color Depth	24-bit 16.7M	24-bit 16.7M	24-bit 16.7M	16-bit 64K	16-bit 64K			
3-bit Alpha Channel Transparency	•	•	•					
Synapse Image Rendering and Multimode Objects	•	•	•	•	•			
Dynamic Text and Animation	•	•	•	•	•			
Dynamic Graphics and PNG Translucency	•	•	•					
Dynamic Menu Objects								
Viemory								
RAM	128MB	128MB	128MB	8MB	8MB			
Flash		64MB		8MB				
	64MB		64MB	QINID	8MB			
Memory Card Slot	up to 4GB	up to 4GB	up to 4GB					
Maximum Project Size	160MB	160MB	160MB	7MB	7MB			
Annotation & PC								
Windows XP Embedded OS								
Neb Browser and Media Player, Remote Desktop, /oIP, NetMeeting, Yahoo! Widgets, MS Office and Adobe Document Viewers ⁶								
Annotation								
Keyboard/Mouse Input								
Fouch-the-PC								
Video/RGB								
Scalable Windows	1	1	1	1	1			
Hardware Connections	QM, CH, BNC1	QM, CH, BNC1	QM, CH, BNC ¹	CH, BNC	CH, BNC			
Composite	•	•	•	•	•			
S-Video	•	•	•	•	•			
Component	•	•	•					
HDTV up to 1080i		•						
RGB up to 1600 x 1200								
Streaming Motion-JPEG								
Media Player (Multiple Formats)								
Display Output								
Audio								
Amplified Speakers and Microphone	•	•	•	•	•			
NAV Sound File Audio Feedback	•	•	•	•	•			
Network								
Dresnet	•	•	•	•	•			
				•	•			
Ethernet Ni-Fi ³	•	•	•					
Buttons								
Jookut Cottkowo	4	4	4					
-				5	5			
-								
Programmable, Engravable Hard Buttons								
Programmable, Engravable Hard Buttons Mounting	•	•	•	•	•			
Programmable, Engravable Hard Buttons Mounting Wall or Lectern Mount ⁴		• 9U	• 8U	• 6U	• 5U			
Programmable, Engravable Hard Buttons Mounting Wall or Lectern Mount ⁴ Rack Mount ⁴	•							
Programmable, Engravable Hard Buttons Mounting Wall or Lectern Mount ⁴ Rack Mount ⁴ Finishes	•							
Backlit Softkeys Programmable, Engravable Hard Buttons Mounting Wall or Lectern Mount ⁴ Rack Mount ⁴ Finishes White or Black Armond	• 9U	9U	80	6U	5U			

¹ Connections via outboard IMC interface module (included)

² Also supports coaxial connection

³ Wireless NIC required

⁴ Appropriate mounting accessory(ies) required

⁵ Rack mount provided by others

⁶ See product spec for a complete list of embedded applications

This chart intended for summary comparison only; see each product specification for complete information.

Isys Wall Mount Touchpanels

Isys G-Series Wall Mount TPs

Isys i/O Wall Mount Touchpanel Media Centers

TPS-2000L	TPS-4L	TPS-15G-QM-L	TPS-12G-QM-L	TPMC-17-QM-L	TPMC-15-QM-L	TPMC-17-CH-L	TPMC-15-CH-L
5"	3.6"	15"	12"	17"	15"	17"	15"
~4:3	4:3 QVGA	4:3 XGA	4:3 SVGA	15:9 WXGA	4:3 XGA	15:9 WXGA	4:3 XGA
320 x 234	320 x 240	1024 x 768	800 x 600	1280 x 768	1024 x 768	1280 x 768	1024 x 768
16-bit 64k	16-bit 64k	24-bit 16.7M	18-bit 256k	24-bit 16.7M	24-bit 16.7M	24-bit 16.7M	24-bit 16.7M
16-bit 64K	16-bit 64K	24-bit 16.7M	24-bit 16.7M				
		•	•	•	•	•	٠
•	•	•	•	•	•	•	•
•	•	•	•	•	•	•	•
	•	•	•	•	•	•	•
				•	•	•	•
	10110	100115					
8MB	16MB	128MB	128MB	512MB	512MB	512MB	512MB
2MB	8MB	64MB	64MB	512MB	512MB	512MB	512MB
1 540	7140	up to 4GB	up to 4GB				
1.5MB	7MB	160MB	160MB	190MB	190MB	190MB	190MB
				•	•	•	
				•	•	•	•
		Live Only	Live Only	MediaMarker	MediaMarker	MediaMarker	MediaMarker
				USB	USB	USB	USB
		•	•	•	•		
1		2	2	2	2	2	2
CH ²		QM	QM	QM	QM	CH, BNC ¹	CH, BNC ¹
•		•	•	•	•	•	•
•		•	•	•	•	•	•
		•	•	•	•	•	•
		•	•	•	•	•	•
		•	•	•	•		
				•	•	•	•
				•	•	•	•
		•	•	•	•		
•		•	•	•	•	•	•
•	•	•	•	•	•	•	•
•		•			•		•
-	•	•	•	•	•	•	•
				•	•	•	•
		4	4	4	4	4	4
10	10						
						_	
• •	•	• 9U	• 8U	• 9U	• 9U	• 9U	• 9U
•	•	30	00	30	90	90	30
•	•	•	•	•	•	•	•
•	٠						
•	•						

